

# HC

| <b>Imperial</b>                 | <b>79250</b>                | <b>79350</b>                |
|---------------------------------|-----------------------------|-----------------------------|
| Blade Width                     | 9'                          | 10'                         |
| Moldboard Options               | Powder-Coated Steel         | Powder-Coated Steel         |
| Blade Type                      | Straight Blade              | Straight Blade              |
| Vehicle Compatibility           | Truck Class 4 - 7 (low-end) | Truck Class 4 - 7 (low-end) |
| Approx. Weight* (Without Mount) | 1,178 lbs                   | 1,312 lbs                   |
| Plowing Width (Full Angle)      | 7'11"                       | 8'10"                       |
| Blade Height                    | 34"                         | 34"                         |
| Blade Thickness                 | 11 ga                       | 11 ga                       |
| Trip Springs                    | 6                           | 6                           |
| Ribs                            | 8                           | 8                           |
| Lift Cylinder                   | 1¾" x 10"                   | 1¾" x 10"                   |
| Angling Rams                    | 2" x 12½"                   | 2" x 12½"                   |
| Cutting Edge                    | ½" x 6" (Standard)          | ½" x 6" (Standard)          |
| Mount Type                      | Minute Mount® 2             | Minute Mount® 2             |

| <b>Metric</b>                   | <b>79250</b>                  | <b>79350</b>                  |
|---------------------------------|-------------------------------|-------------------------------|
| Models                          | 79250                         | 79350                         |
| Blade Width                     | 2.74 m                        | 3.05 m                        |
| Moldboard Options               | Powder-Coated Steel           | Powder-Coated Steel           |
| Blade Type                      | Straight Blade                | Straight Blade                |
| Vehicle Compatibility           | Truck Class 4 - 7 (low-end)   | Truck Class 4 - 7 (low-end)   |
| Approx. Weight* (Without Mount) | 534 kg                        | 594 kg                        |
| Plowing Width (Full Angle)      | 2.41 m                        | 2.67 m                        |
| Blade Height                    | 86.36 cm                      | 86.36 cm                      |
| Blade Thickness                 | 11 ga                         | 11 ga                         |
| Trip Springs                    | 6                             | 6                             |
| Ribs                            | 8                             | 8                             |
| Lift Cylinder                   | 4.44 cm x 25.4 cm             | 4.44 cm x 25.4 cm             |
| Angling Rams                    | 5.08 cm x 31.75 cm            | 5.08 cm x 31.75 cm            |
| Cutting Edge                    | 1.27 cm x 15.24 cm (Standard) | 1.27 cm x 15.24 cm (Standard) |
| Mount Type                      | Minute Mount® 2               | Minute Mount® 2               |

\* Does not include vehicle mount (approx. 60 lbs - 184 lbs for straight blades). Please refer to the eMatch program for specific vehicle applications.