

# XLS(TM)

<b>Imperial</b>	<b>74810</b>	<b>79810</b>	<b>74850</b>	<b>79850</b>
Blade Size	8'-10'	8'-10'	8'6"-11'	8'6"-11'
Moldboard Options	Stainless Steel	Powder-Coated Steel	Stainless Steel	Powder-Coated Steel
Blade Type	Adjustable Winged Blade	Adjustable Winged Blade	Adjustable Winged Blade	Adjustable Winged Blade
Vehicle Compatibility	Truck Class 2 - 5 & Tractors	Truck Class 2 - 5 & Tractors	Truck Class 2 - 6	Truck Class 2 - 6
Approx. Weight* (Without Mount)	1,078 lbs	1,078 lbs	1,140 lbs	1,140 lbs
Plowing Width	Retracted: 7'2" Extended: 9' Scoop: 7'11"	Retracted: 7'2" Extended: 9' Scoop: 7'11"	Retracted: 7'11" Extended: 10'6" Scoop: 9'6"	Retracted: 7'11" Extended: 10'6" Scoop: 9'6"
Blade Width	Retracted: 8' Extended: 10' Scoop: 8'10"	Retracted: 8' Extended: 10' Scoop: 8'10"	Retracted: 8'6" Extended: 11' Scoop: 9'10"	Retracted: 8'6" Extended: 11' Scoop: 9'10"
Blade Height	At Center: 31" At End: 35"	At Center: 31" At End: 35"	At Center: 31" At End: 36"	At Center: 31" At End: 36"
Blade Thickness	14 ga	14 ga	14 ga	14 ga
Trip Springs	4	4	4	4
Vertical Ribs	10	10	10	10
Lift Cylinder	1¾" x 10"	1¾" x 10"	1¾" x 10"	1¾" x 10"
Angling Rams	1½" x 10"	1½" x 10"	1½" x 10"	1½" x 10"
Blade Cutting Edge	½" x 6" Steel (Standard)	½" x 6" Steel (Standard)	½" x 6" Steel (Standard)	½" x 6" Steel (Standard)
Wing Cutting Edge	1½" x 9" Poly (Standard)	1½" x 9" Poly (Standard)	1½" x 9" Poly (Standard)	1½" x 9" Poly (Standard)
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

<b>Metric</b>	<b>74810</b>	<b>79810</b>	<b>74850</b>	<b>79850</b>
Models	74810	79810	74850	79850
Blade Size	8'-10'	8'-10'	8'6"-11'	8'6"-11'
Moldboard Options	Stainless Steel	Powder-Coated Steel	Stainless Steel	Powder-Coated Steel
Blade Type	Adjustable Winged Blade	Adjustable Winged Blade	Adjustable Winged Blade	Adjustable Winged Blade
Vehicle Compatibility	Truck Class 2 - 5 & Tractors	Truck Class 2 - 5 & Tractors	Truck Class 2 - 6	Truck Class 2 - 6
Approx. Weight* (Without Mount)	488 kg	488 kg	516 kg	516 kg
Plowing Width	Retracted: 2.18 m Extended: 2.74 m Scoop: 2.41 m	Retracted: 2.18 m Extended: 2.74 m Scoop: 2.41 m	Retracted: 2.41 m Extended: 3.20 m Scoop: 2.90 m	Retracted: 2.41 m Extended: 3.20 m Scoop: 2.90 m
Blade Width	Retracted: 2.44 m Extended: 3.05 m Scoop: 2.69 m	Retracted: 2.44 m Extended: 3.05 m Scoop: 2.69 m	Retracted: 2.59 m Extended: 3.35 m Scoop: 3 m	Retracted: 2.59 m Extended: 3.35 m Scoop: 3 m
Blade Height	At Center: 78.74 cm At End: 88.9 cm	At Center: 78.74 cm At End: 88.9 cm	At Center: 78.74 cm At End: 91.44 cm	At Center: 78.74 cm At End: 91.44 cm
Blade Thickness	14 ga	14 ga	14 ga	14 ga
Trip Springs	4	4	4	4
Vertical Ribs	10	10	10	10
Lift Cylinder	4.45 cm x 25.40 cm	4.45 cm x 25.40 cm	4.45 cm x 25.40 cm	4.45 cm x 25.40 cm

## XLS(TM)

---

Angling Rams	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Blade Cutting Edge	1.27 cm x 15.24 cm Steel (Standard)	1.27 cm x 15.24 cm Steel (Standard)	1.27 cm x 15.24 cm Steel (Standard)	1.27 cm x 15.24 cm Steel (Standard)
Wing Cutting Edge	3.81 cm x 22.86 cm Poly (Standard)	3.81 cm x 22.86 cm Poly (Standard)	3.81 cm x 22.86 cm Poly (Standard)	3.81 cm x 22.86 cm Poly (Standard)
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

*\* Does not include vehicle mount (approx. 60 lbs for winged blades). Please refer to the eMatch program for specific vehicle applications.*